

FCS-5212, GEMINI IP CAMERA, 6-MP, H.265, 802.3AF, POE, IR LEDS, INDOOR/OUTDOOR, TWO-WAY AUDIO

Product Images



Short Description

- 6-Megapixel resolution
- Features WDR (Wide Dynamic Range) to enhance visibility under extremely bright or dark environments
- Built-in Micro SDHC/SDXC card slot for local storage
- Built-in infrared LEDs for night viewing up to 60m
- Supports 3 video streams simultaneously
- Video compression: H.264, H.265, MJPEG
- Supports 4.3X optical zoom

- Weatherproof IP67-rated housing

Description

The LevelOne FCS-5212 is a fixed-position outdoor camera offering an ultra-reliable, cost-effective solution for outdoor IP surveillance networks, and is rated at IP66 to operate within rain, extreme heat, snow, dust and humid conditions. Offering clear, sharp imagery with 6-Megapixel resolution and the versatility of 802.3at standard PoE to transfer power and data via a single Cat.5 cable, the LevelOne FCS-5212 should be an essential part of any security deployment that requires smart, reliable outdoor cameras.

Additional Information

Color	White
EAN	4015867229569
Model Number	FCS-5212
Features	Event: - Motion detection (human and vehicle targets classification), video tampering alarm, exception - Line crossing detection, intrusion detection - Supports human and vehicle targets classification - Face detection Privacy masks: -4 programmable polygon. Image Enhancement: - BLC, HLC, 3D DNR Image Settings: - Rotate, mirror, privacy mask, saturation, brightness, contrast, sharpness, gain
2-way audio	Yes
DI/DO	Yes
IR LED for night vision	Yes
Max. Resolution	6 Megapixels
Resistance	Weatherproof, Vandalproof
IP Camera series	GEMINI
Camera Type	Bullet
Zoom type	Motorization
PoE Supported	Yes
Approval and Compliance	CE/FCC/UL
Compatibility	ONVIF
Operating humidity	0% RH ~ 95% RH
Operating temperature	-30°C ~ 60°C
Supported browsers	Plug-in required live view: IE 10, IE 11 Plug-in free live view : Chrome 57.0+, Firefox 52.0+ Local service: Chrome 57.0+, Firefox 52.0+
Compatible operating systems	Option accessory Mounting Kit : CAS-7303 Pole Mount CAS-7307 Corner mount CAS-7311 Junction Box CAS-7312 Power intake box
Storage humidity	0% RH ~ 95% RH

Storage temperature	-30°C ~ 70°C
Package Contents	FCS-5212 Screw Kit
Dimensions (W x D x H)	308.5x97.9x93
Product weight (kg)	1.385
Angle of view (°)	Horizontal FOV 106° to 32°, Vertical FOV 56° to 18°, Diagonal FOV 127° to 37°
Audio format	G.711/G.722.1/G.726/MP2L2/PCM
Image sensor	1/2.4" Progressive Scan CMOS
Indicators	Power Link/act
IR cut filter	No
IR range	60 Meters
Lens	Varifocal Motorized Lens, 2.8 to 12 mm
Minimum illumination (lux)	Color: 0.005 Lux @ (F1.6, AGC ON), B/W: 0 Lux with IR
Mount	Wall mount
Optical zoom	4.3 Motorized
Port Configuration	RJ-45,Power plug ,DI/DO
Power consumption	12 VDC ± 25%, 1.08 A, max. 13 W, Ø5.5 mm coaxial power plug PoE: 802.3at, Class 4, 42.5 V to 57 V, 0.36 A to 0.27 A, max. 15 W
Power supply	12 VDC ± 25%, PoE: 802.3at
Resolution	Main Stream 50 Hz: 20 fps (3200 × 1800) 25 fps (2688 × 1520, 1920 × 1080, 1280 × 720) 60 Hz: 20 fps (3200 × 1800) 30 fps (2688 × 1520, 1920 × 1080, 1280 × 720) Sub-Stream 50 Hz: 25 fps (1280 × 720, 640 × 480, 640 × 360) 60 Hz: 30 fps (1280 × 720, 640 × 480, 640 × 360) Third Stream 50 Hz: 10 fps (1920 × 1080, 1280 × 720, 640 × 480, 640 × 360) 60 Hz: 10 fps (1920 × 1080, 1280 × 720, 640 × 480, 640 × 360)
Shutter time	1/3 s to 1/100,000 s
Standards	IEEE 802.3 10-BASE-T, Ethernet IEEE 802.3u 100-BASE-TX, Fast Ethernet IEEE 802.3af Power over Ethernet (PoE) TCP, UDP, HTTP, HTTPS, DHCP, PPPoE, RTP, RTSP, IPv6, DNS, DDNS, NTP, ICMP, ARP, IGMP, SMTP, FTP, UPnP, SNMP, Bonjour

Storage capacity	Built-in memory card slot, support micro SD card, up to 256 GB
Video format	H.265/H.264/MJPEG
Weatherproof rating	IP67